
### Reminder


#### Rave


- Reconstruction in an Abstract, Versatile Environment
- vertex reconstruction toolkit with input of reconstructed track

### First look

- randomly select N simulated tracks from pool
  (mu+, lηl<0.5 (flat), 1<p<sub>T</sub><40 GeV/c (flat), generated vertex (0,0,0))</li>
- tracking with PHGenFit and extract parameters at beam line put tracks into the RAVE vertex finder (defaults setting) currently using self-package, but will move to GFRave
- scan N track(s) from 1 to 50, 2k events for each N track(s)









# 2 vertices finding test

- generate 5 tracks at each z position of z=0 and z=z<sub>2nd</sub> cm
- scan  $z_{2nd}$  from 0.1 cm to 1.5 cm with 0.1 cm interval (1k try for each  $z_{2nd}$ )





need to check number of vertices is set to 2 in multi-vertices mode

# 2 vertices finding test

- generate 2 tracks at each z position of z=0 and z=z<sub>2nd</sub> cm
- scan z<sub>2nd</sub> from 0.1 cm to 1.5 cm with 0.1 cm interval (1k try for each z<sub>2nd</sub>)
- scan  $z_{2nd}$  from 0.01 cm to 0.15 cm with 0.01 cm interval (1k try for each  $z_{2nd}$ )

